

## MOBILE LINE

A wide range of resistant and tough mobile light towers with high quality standards. This range is made-up of light towers equipped with different kinds of road or site-tow trailers, for use in the most hard working environments. The smallest models are equipped with a practical manual hand trolley allowing a single operator to manouvre quickly and safely. They are ideal for use in areas where illumination needs to be frequently repositioned.



## SPECIAL LINE

Generac® Tower Light does take requests for specially designed models and will evaluate the viability of those requests on a case-by-case basis. Also available are a range of alternative products, such as light towers with double telescopic mast, extended height masts up to 20 metres and models placed on vehicles, skids or other special trailers.



**GENERAC®** | **MOBILE PRODUCTS**

**Generac Mobile Products Srl**  
Part of Generac Power Systems, Inc.  
Via Stazione, 3 bis - 27030 Villanova d'Ardenghi (PV) - Italy  
Tel +39.0382.567011 - gmp.srl@generac.com  
[www.towerlight.com](http://www.towerlight.com) | [www.generacmobileproducts.com](http://www.generacmobileproducts.com)

EN\_TLFOLD\_1706\_r1.2

## LIGHT TOWERS

**GENERAC®** | **TOWER LIGHT**

## HYBRID LINE

Generac® Tower Light is always looking for new, environmentally friendly solutions and that is what led us to create a specific line of light towers equipped with hybrid technologies. The machines in this innovative line are equipped with a backup diesel generator and a rechargeable battery pack which present considerable advantages in terms of fuel savings, noise reduction and CO<sub>2</sub> emissions.



## STATIONARY LINE

A range of static light towers that can be mounted on a base or fastened horizontally or vertically on a fixed structure like a container. Silent and compact models with different height masts, available with different kinds of floodlights, these light towers ensure high versatility in different working areas. Ideal solution for fixed position use.





**VT-Hybrid**

- Height: 8,5 m
- Floodlights: 4x150W LED
- Running time: 650+ hours
- MPnano digital controller
- Site-tow or road trailer
- Low noise
- Engine: Yanmar L70N
- Illuminated area: 2500 m<sup>2</sup>

**CUBE<sup>+</sup> Hybrid**

- Height: 8,4 m
- Floodlights: 4x150W LED
- Running time: 700+ hours
- MPnano digital controller
- Mounted on base
- Top accessibility
- Engine: Yanmar L70N
- Illuminated area: 2500 m<sup>2</sup>

**Hydro Power Box Hybrid**

- Height: 8,3 m
- Floodlights: 4x150W LED
- Running time: 1200+ hours
- MPnano digital controller
- Vandalism-proof solution
- Top accessibility
- Engine: Yanmar L70N
- Illuminated area: 2500 m<sup>2</sup>

**CUBE<sup>+</sup>**

- Height: 8,4 m
- 4x1000W MH or 4x300W LED
- Hydraulic lifting system
- GTL01 digital controller
- Tradition: Kubota D1105 engine
- Super: Kubota Z482 engine
- Empty: without engine
- Illuminated area: 4200 m<sup>2</sup>

**HYDRO POWER BOX**

- Height: 8,3 m
- 4x1000W MH or 4x300W LED
- Hydraulic lifting system
- GTL01 digital controller
- Vandalism-proof for events
- Tradition: Kubota D1105 engine
- Super: Kubota Z482 engine
- Empty: without engine
- Illuminated area: 4200 m<sup>2</sup>

**CTF 10**

- Height: 10 m
- 4x1000W MH or 4x150W LED or 4x290W LED
- Manual lifting system
- Extremely compact
- Without engine
- Illuminated area: 4600 m<sup>2</sup> (4x1000W MH) 3000 m<sup>2</sup> (4x150W LED) 4000 m<sup>2</sup> (4x290W LED)

**CTF 5/7/9**

- Height: 5,5, 7 or 9 m
- 4x500W or 4x1000W or 4x1500W Hal
- Manual lifting system
- Fastening on side
- Illuminated area: 625 m<sup>2</sup> (5,5 m) 1500 m<sup>2</sup> (7 m) 2000 m<sup>2</sup> (9 m)

**CTF 5**

- Height: 5 m
- 4x400W MH or 4x150W LED
- Manual lifting system
- Fastening on base
- Illuminated area: 1600 m<sup>2</sup> (4x400W MH) 1800 m<sup>2</sup> (4x150W LED)

**VT1**

- Height: 8,5 m
- Floodlights: 4x1000W MH
- Hydraulic lifting system
- GTL01 digital controller
- Site-tow or road trailer
- Engine 1: Kubota D1105
- Engine 2: Yanmar 3TN
- Illuminated area: 4200 m<sup>2</sup>

**V20**

- Height: 8,5 m
- Floodlights: 4x300W LED
- Hydraulic lifting system
- GTL01 digital controller
- Site-tow or road trailer
- Engine: Kubota Z482
- Illuminated area: 4200 m<sup>2</sup>

**VT-MINE**

- Height: 8,5 m
- Floodlights: 6x300W LED
- Hydraulic lifting system
- GTL01 digital controller
- Special for mining sector
- Engine: Kubota D1105
- Illuminated area: 4900 m<sup>2</sup>

**HYDRO**

- Height: 8,5 m
- 4x1000W MH or 4x300W LED
- Hydraulic lifting system
- 10 or 22 kVA generator (Perkins)
- Site-tow trailer
- Illuminated area: 4200 m<sup>2</sup>

**VT8**

- Height: 8 m
- Floodlights: 4x1000W MH
- Manual lifting system
- Site-tow or road trailer
- Engine 1: Kubota D1105
- Engine 2: Yanmar 3TN
- Illuminated area: 4200 m<sup>2</sup>

**VMAX**

- Height: 8 m
- Floodlights: 4x1000W MH
- Manual lifting system
- Reinforced frame
- Liquid containment tank
- Long running time
- Engine 1: Kubota D1105
- Engine 2: Yanmar 3TN
- Illuminated area: 4200 m<sup>2</sup>

**VTevo**

- Height: 8 m
- Floodlights: 4x290W LED
- Manual lifting system
- Compact shape
- Engine 1: Kubota Z482
- Engine 2: Yanmar L70N
- Illuminated area: 3600 m<sup>2</sup>

**STRONG**

- Height: 8,5 m
- 4x1000W MH or 4x300W LED
- Manual lifting system
- 10 or 22 kVA generator (Perkins)
- Site-tow trailer
- Illuminated area: 4200 m<sup>2</sup>

**Linktower T3**

- Height: 6,3 m
- 4x400W MH or 4x150W LED
- Manual lifting system
- Linkable in series
- ATEX version available
- Illuminated area: 2100 m<sup>2</sup> (MH) 2300 m<sup>2</sup> (LED)

**MM6**

- Height: 5,5 m
- 4x400W MH or 4x150W LED
- Manual lifting system
- 5 or 6 kVA generator (Honda / Yanmar)
- Hand trolley
- Illuminated area: 1600 m<sup>2</sup> (MH) 1800 m<sup>2</sup> (LED)

**MT1**

- Height: 5,3 m
- 4x400W MH or 4x150W LED
- Manual lifting system
- Extremely compact
- Hand trolley version available
- Engine: Yanmar L70N
- Illuminated area: 1600 m<sup>2</sup> (MH) 1800 m<sup>2</sup> (LED)

**TF 5.5 / 7**

- Height: 5,5 m or 7 m
- 4x500W or 2x1500W Hal
- Manual lifting system
- On tripod
- Illuminated area: 625 m<sup>2</sup> (5,5 m) 1200 m<sup>2</sup> (7 m)

