


Technical sheet

1650 RT

Compact Track Loaders

Weight and dimensions	Metric
h27 - Overall Operating Height – Fully Raised	4008 mm
h28 - Height to Hinge Pin – Fully Raised	3038 mm
dp1 - Reach - Fully Raised	641 mm
a5 - Dump Angle at Full Height	39 °
h29 - Dump Height	2329 mm
a4 - Maximum Rollback Angle - Fully Raised	98 °
h17 Overall Height to Top of ROPS	1969 mm
l16 - Overall Length with Bucket	3205 mm
h31 - Specified Height	1638 mm
r4 - Reach at Specified Height	1638 mm
a17 - Dump Angle at Specified Height	73 °
a13 - Maximum Rollback Angle At Ground	28 °
d5 - Carry Position	198 mm
a14 - Maximum Rollback Angle at Carry Position	28 °
h32 - Digging Position - Below Ground	53 mm
a2 - Departure Angle	28 °
m4 - Ground Clearance to Chassis	184 mm
Track Gauge	1356 mm
b20 - Track Shoe Width	320 mm
y2 - Crawler Base	1265 mm
b1 - Overall Width - Less Bucket A	1676 mm
e1 - Bucket Width	1676 mm
b18 - Clearance Circle – Front with Bucket	1979 mm
Maximum Rollback at Specified Height	68.60 °
Angle of Approach	90 °
Grouser Height	25 mm
Operating Capacity at 35% Tipping Load	748 kg
Operating Capacity at 50% Tipping Load	1069 kg
Operating Weight	3693 kg
Track width	320 mm
Performances	
Ground Speed - Single Speed	10.50 km/h
Ground Speed - Two Speed	16.10 km/h
Drawbar Pull	4345 kg
Bucket Breakout - Tilt Cylinder	1.92 kg
Bucket Breakout - Lift Cylinder	2295 kg
Engine	
Make	Yanmar
Model	4TNV98C-NMS2
Motor type	Interim Tier IV
Gross Power	69.90 hp / 52.10 kW
Net Power	51 hp / 68.40 kW
Maximum Torque	241 Nm at -
Battery (CCA)	12 V / -
Starter	69.90 hp
Alternator	69.90 hp / 1.40 kW
Hydraulics	
Auxiliary Hydraulic Flow – Rated Speed	71.40 l/min
High-Flow Auxiliary Hydraulics – Option	119 l/min
Tank capacities	
Oil Pan Capacity	10.40 l
Reservoir Capacity	62.50 l
Hydraulic Reservoir Tank	41.60 l
Displacement / cylinders	3.30 l / 4
Engine coolant	14.40 l

Dimensional drawing



Equipments

Engine	
Engine Auto-Shutdown System	Standard
Engine Alert System with Error Display	Standard
Glowplugs Starts Assist	Standard
Dual-Element Air Cleaner with Indicator	Standard
Hydraulics	
Auxiliary Hydraulics	Standard
High-Flow Auxiliary Hydraulics	Optional
Undercarriage	
Elevated Planetary Final Drives	Standard
Single Flange Front/Dual Flange Rear Idlers	Standard
Rubber Track Undercarriage System	Standard
Servo-Controlled Hydrostatic Drive	Standard
Structure	
Combination Radiator & Hydraulic Oil Cooler	Standard
Anti-Vandalism Lock Provisions	Standard
Mechanical Lift Cylinder Lock	Standard
Operator station	
ROPS/FOPS Level II Overhead Guard	Standard
Pressurized Cab Enclosure with A/C	Optional
Multi-Function Function Display Screen	Standard
Electronic Attachment Control - 14-Pin Connector	Optional
Foot Throttle	Standard
Full-Suspension Seat	Standard
Suspension Seat - Air Ride	Optional
Performance	
All-Tach® Attachment Mounting System	Standard
Power-A-Tach® Attachment Mounting System	Optional
Selectable Self-Leveling Hydraulic Lift Action 4	Optional
Back-Up Alarm	Optional
IdeaTrax™ Automatic Track Tensioning System	Standard
Two-Speed Hydrostatic Drive System	Standard

Your dealer :



Siège Social

B.P. 249 - 430 rue de l'Aubinière - 44158 Ancenis Cedex - France

Tel: 00 33 (0)2 40 09 10 11 - Fax: 00 33 (0)2 40 09 10 97

manitou.com



This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only. MANITOU BF SA - Limited company with board of directors - Share capital: 39,547,824 euros - 857 802 508 RCS Nantes