

## **Y**20 HYPER















OMNIA® LED TECHNOLOGY
The special Hyper version is equipped with
Omnia® LED Technology. Floodlights are
installed on a fully adjustable bracket allowing
the operator to point the floodlights in any
direction and provide total 360 illumination.
Floodlights are also available with anti-glare
system.




## **DIGITAL CONTROLLER**

A digital controller specifically designed exclusively for our Generac lighting towers. Every function of the machine can be controlled and managed from a single digital panel.

## LONG RUNNING TIME

Thanks to the V20's fuel saving features such as the small engine and LED lamps, this model can run up to 167 hours without refuelling.



The **V20 HYPER** lamps can be equipped with anti-glare shells. The anti-glare floodlights are a perfect solution for roadworks and other applications where there is a risk of glaring workers and passers-by.

TECHNICAL DATA		<b>Y</b> ∞ HYPER Y	<b>Y</b> ≥o HYPER P
Lifting system	-	Hydraulic	Hydraulic
Min. dim.	cm	2200 x 1400 x 2440	2200 x 1400 x 2440
Max. dim.	cm	2200 x 1850 x 8500	2200 x 1850 x 8500
Dry weight	kg	980	980
Lamps power	W	4 x 320	4 x 320
Lamps type	-	LED	LED
Certified illuminated area	m²	4,200	4,200
Total lumen	Lm	184,000	184,000
Mast rotation	o	340	340
Certified wind speed resistance	km/h	110	110
Tank capacity	liter	110	110
Engine model	-	Yanmar 2TNV-70 2 cyl. @1500/1800 rpm	Perkins 402D-05 2 cyl. @1500/1800 rpm
Engine cooling	W=Water/A=Air	W	W
Alternator	kVA/V/Hz	5/220/50 - 5/240/60	5/220/50 - 5/240/60
Outlet socket	kVA/V/Hz	2/220/50 - 2/240/60	2/220/50 - 2/240/60
Inlet plug	A/V/Hz	16/220/50 - 16/240/60	16/220/50 - 16/240/60
Running time	h	167	167
Avg. sound pressure level	dB(A) @ 7m	58	58
Trailers available	-	Road trailer or site-tow trailer	Road trailer or site-tow traile



## **Generac Mobile Products Srl**

Part of Generac Power Systems, Inc.
Via Stazione, 3bis - 27030 Villanova d'Ardenghi (PV) - Italy
Tel +39 0382 567011 - gmp.srl@generac.com
www.towerlight.com | www.generacmobileproducts.com